

SV-CLCD56-500
SV-CLCD56-620



This collision avoidance camera system supports three cameras, as well as the ability to connect to a mobile digital video recording system. The camera's infrared illuminators automatically activate as needed providing you with optimal image quality.

When the vehicle starts or is placed in reverse, the system activates. With the camera's built-in microphone, people behind the vehicle can communicate directly with you alerting you to possible hazards.

Features

- Low reflection 5.6-inch monitor with three camera inputs and switchable camera views
- Camera has integrated auto iris and microphone with water-resistant housing
- Eleven advanced infrared illuminators with automatic sensor for better image quality in low-light conditions



Control Box SV-LDCB-PKKIT

Power Requirement: 10 ~ 32 VDC.
Operating temperature: 14°F ~ to 176°F
Dimensions: 7.3 in. x 1.1 in. x 4.6 in.

SPECIFICATIONS	
SV-LCD56 Monitor	
LCD System	5.6-inch
Video System	NTSC standard signal
Auto Dimmer	Selectable auto/manual
OSD Controls	Bright, contrast, color, tint, image select CA1 (mirror view/true view), auto scan time, scale on/off
Resolution	960 x 234 pixels
Impact Rating	4G
Sync System	Internal
Power Requirement	12 VDC provided by control box
Power Consumption	12W
Operating Temperature	32°F ~ 122°F (0°C ~ 50°C)
Dimensions (w x h x d)	6.8 in. x 4.5 in. x 1.1 in. (172 mm x 115 mm x 28 mm)
Weight	2.2 lbs. (1.0 kg)
SV-620A Color/SV-500A Black and White Camera	
Image Sensor	1/3 inch interline transfer CCD
Signal Format	NTSC
Picture Elements	270,000 pixels
Field of View	130°
Sync System	Internal
Horizontal Resolution	330 TV lines (color) 380 TV lines (black and white)
Minimum Illumination	0 lux
Signal-to-Noise Ratio	50 dB minimum (color - AGC off) 47 dB minimum (black and white - AGC off)
Impact Rating	10G
Power Requirement	12 VDC provided by control box
Operating Temperature	-22°F ~ 122°F (-30°C ~ 50°C)
Dimensions (w x h x d)	2.7 in x 1.6 in x 2.0 in (69 mm x 41 mm x 50.7 mm)
Weight	.80 lb. (0.3 kg)



Optional Accessories



LCD RAM Mount and Control Box

Safety Vision offers a variety of monitor mounting options and control boxes. The ram mount is ideal for heavy duty operations and the audio/video control box has four camera inputs and can connect a recording unit.



Camera Cables and Cages

Safety Vision offers a wide range of cable types and lengths from 16 feet to over 100 feet. Sectional cables provide ease of installation and repair. Heavy duty operations benefit from the addition of camera cages for enhanced camera protection.

Warranty Agreement

Safety Vision's standard warranty for new items is one year. Extended warranties and advance replacement agreements also are available: Ask your sales or customer service representative for details.



REPRESENTANTE NO BRASIL
MARPRESS - MARTE COMERCIAL LTDA
RUA BARBOSA REZENDE 257 - BAIRRO GRAJAU
BELO HORIZONTE - MINAS GERAIS - CEP30430-680
tel: 31.337.14334 | fax: 31.337.11725 | celular: 31.910.76288
marpress@marpressbrasil.com.br

www.marpressbrasil.com.br

**SAFETY
VISION®**

Mobile video solutions for enhanced safety