

# POS X

POINT OF SALE  
PERFECTED

## XPC600 SERIES

FANLESS ALL-IN-ONE TOUCHPC

Designed to be seen and not heard, the XPC600 offers cutting edge performance and rock-solid stability. Grease, lint, and dirt are no longer an issue due to its fanless design. The XPC600's solid die-cut aluminum heatsink encompasses the entire backside of the unit, allowing for cooler operating temperatures at higher CPU speeds. Perfect for Restaurants or any location where noise is at a premium, the XPC600 is the system of choice in Fanless technology.



### KEY FEATURES


- CPU: Intel 1.6GHz Celeron M ~ 1.73GHz Pentium M
- Memory: 1GB DDR II RAM
- Optional integrated MSR and Customer Display
- Rugged spill resistant metal housing
- Bump-free 90-degree tilting base
- Silent fanless operation
- Additional VGA output
- 3 year warranty



ALL-IN-ONE TOUCHPC

# XPC600 Series Specifications

PART NUMBER	XPC600-C	XPC600-P
<b>MOTHERBOARD</b>	M6 400 MHz FSB	M6 533 MHz FSB
CPU	1.6 GHz Celeron M	1.73 GHz Pentium M
Chip Set	VIA VN800	
System Memory	1GB DDR II 533 MHz	
Video	VN800 Integrated Graphics Max 64 MB	
Audio	VIA VT1613 AC'97 chip on-board	
<b>PORTS</b>		
USB	4 x USB2	
Serial/Com	4 x RS232 optional configurable powered 5V, 12V by Jumper D-Sub 9 Pin Male	
Parallel	Supports SPP/ECP/EPP mode D-sub 25-pins Female	
LAN	1 10/100M RJ45 Wake-From-LAN Support	
2nd VGA	1 x 15 pin D-Sub Female	
Cash Drawer	2x RJ12 Cash Drawer port 12v/24v	
Mouse	1 x PS/2	
Keyboard	1 x PS/2	
Audio Out	1 x 3.5mm Audio-Jack	
Mic	1 x 3.5mm Audio-Jack	
<b>HARD DRIVE</b>	1 x 2.5" 160 GB	
<b>PHYSICAL</b>		
Housing	Die Cut Aluminum Basket, ABS Bezel	
Weight with Base	19 lbs	
Dimensions with Base	15" (W) x 10.0" (D) x 13" (H)	
Dimensions without Base	15" (W) x 3.5" (D) x 12" (H)	
Tilt Angle	0° to 90°	
Optional Mounting	VESA 75 x 75 mm	
Housing Color	Black	
LCD Display	15" 1024 x 768 pixel, 16.7M colors 250 nit	
Touch Screen	5-Wire Resistive, 35+ million taps per location	
<b>ELECTRICAL</b>	200W	
<b>ENVIROMENTAL</b>		
Temperature	32° F to 114° F operating	
Humidity	10% - 95% non-condensing	
Shock Resistance	Operating shock 5g	
<b>WARRANTY</b>	3 Year Limited	
<b>CERTIFICATIONS</b>	FCC Class A, CE, RoHs	



## ACCESSORIES

XM135U	3 Track MSR with USB interface
XM135U-BIO	3 Track MSR with USB interface & Fingerprint Authentication
XP2200S	Integrated Customer Display