



# SENIOR TECH CO.,LTD.

No.165,Kang Ning Street, Shichih,Taipei Hsien Taiwan.

TEL:02-26950405 FAX:02-26952745 <http://www.senortech.com>



## APOS 400

2006/09/05

Name	Specification	
Main Board	ST-478E	
CPU Supports	Intel P4 Celeron M 1GHz	
System Memory	256MB up to 2GB DDR 266	
Display Function	Intel 852GM built-in Intel extreme graphic 2 Intel Dynamic Video Memory up to 64MB shared with system	
<b>LCD Touch Panel</b>		
LCD Size	15" TFT LCD	
Resolution	1024 x 768	
Brightness	250 cd/m <sup>2</sup>	
Touch Screen	ELO five-wire Resistive	
<b>Connectivity</b>		
IDE	IDE1: 1 x 44 pins socket for HDD + 1x Compact Flash socket	
LAN	1 x RJ-45 LAN port 10/100M/1GHzbit	Internal 802.11g Wireless LAN (Option)
USB	4x USB2.0 ports	
Serial	5X RJ45 for COM or 3 X RJ45 for COM + 2 X RJ11 for Cash Drawer	
PS/2 KB	1 x Mini Din Jack	
VGA	1 x DB15 Connector	
Audio	1 X Earphone Jack For Line- out	
<b>Mechanical &amp; Environment</b>		
Dimension (W X D X H )	380 X 218 X 354 mm	
Weight	N.W. 7.1Kgs	
Motorized Angel Adjustment	Senor Patent Design	
Smart Features	Internal Smart Battery, Internal Smart Fan	
Infrared Function	Built-in Infrared K/B & mouse Receiver	
Splash Resistant	IP43	
Safety Certifications	FCC / CE / CCC / UL / CB	
Storage temperature	-20°C ~60°C	
Operating temperature	0°~40°C	
Relative Humidity	20%-80% (non-condensing)	
<b>Software</b>		
Operation System	Windows 2000 / XP / Linux / WEPOS	
Self-testing program	Observer software	
<b>Peripheral Options</b>		
Infrared keyboard	Keyboard wedge interface	
Magnetic Card Reader	Single Track, Double Tracks, Triple Tracks	
Smart Card Reader	ISO-7816 compatible	
Finger Print Sensor	Optical Type, 512 dpi	
I-button	Dallas Key	
Modem	56 Kbps Modem	
Customer Display	VFD 20x2 lines Display / LCD Graphic Display	

※NOTE: The product information and specifications are subject to change without notice.