

# POS X

POINT OF SALE  
PERFECTED

barcode scanner

## XI3200BT

### Wireless Bluetooth Barcode Scanner

Wireless Scanning has never been more affordable. Featuring lightning fast scanning speed, extra long battery life, and a light weight ergonomic feel, the XI3200BT the perfect choice for any scanning application desiring the freedom of wireless.

#### **Class 1 Bluetooth Technology**

Featuring true Class 1 Bluetooth connectivity (up to 328'), the XI3200BT provides plenty of range for retail and light industrial applications. Coming standard with a convenient recharging base station, the XI3200BT easily connects to any PC, or can be paired with standard Bluetooth device such as a cell phone, PDA or Mobile Computer.



#### **High Performance Optical Engine**

The XI3200BT features an aggressive optical scan engine engineered with a lightning fast scan rate and an increased depth of field. The result is near-laser performance with the added durability of no moving parts.

#### **Key Features**

- 3 Year Advanced Replacement Warranty
- Reading Distance 1" ~ 14"
- 328' Class 1 Bluetooth Range
- Battery Lasts for over 50,000 Scans
- Ergonomic and Light Weight
- No Moving Parts for Increased Durability

# XI3200BT Specifications

<b>PART NUMBER</b>	XI3200BT	
<b>PERFORMANCE</b>		
Engine	Linear Imaging	
Light Source	Red LED (660nm) 60mm Array Width	
Optical Sensor	2048 pixels	
Depth of Field	2.18" to 14.17" @ 15.6 mil	
Resolution	4 mil	
Scanning Angle	Pitch $\pm$ 60° Skew $\pm$ 60°	
Scan Rate	230 scans per second	
Largest Readable Label Width	7.87"	
Ambient Light Rejection	10000Lux/Max (Fluorescent Light)	
<b>FEATURES</b>		
Supported Symbologies	Code 39/Full ASCII, Codabar, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, Code 93, Code 128, Code 32, Standard Code 39, EAN 128, MSI, EAN 8&13, UPCA & E, Plessey, RSS14, TELEPEN	
Programmable Features	Code ID, Prefix Code, Postfix Code, Length Code, Barcode Type, Buzzer Frequency, ISBN/ISSN/CLSI/UK Plessey Conversion, Keyboard Layout, Inter-Character Delay, Scanning Mode, LanGUAGE Type, Time Out, Baud Rate, Data Bit, Transmission Mode, Character Replace	
<b>BLUETOOTH® CLASS 1</b>		
Radio Frequency	2.4GHz	
Range	328 feet line of site	
<b>PHYSICAL</b>		
	<b>Scanner</b>	<b>Cradle</b>
Weight	5.6 oz $\pm$ 0.35 oz	8 oz $\pm$ 0.35 oz
Housing	ABS	ABS
Dimensions	3.6"(L) x 2.9"(W) x 6.9"(H)	7.92"(L) x 4.37"(W) x 2.76"(H)
Color	Black	Black
<b>ELECTRICAL</b>		
Battery	Lithium-ion 1620mAh	
Operating Time	50,000 scans per charge	
<b>POWER CONSUMPTION</b>	<1200 mW (Operation)	
<b>ENVIROMENTAL</b>		
Temperature	32° - 122° F	
Humidity	20% - 85% non-condensing (operation)	
Shock Resistance	Withstands multiple drops from 6.5' onto a concrete surface	
<b>WARRANTY</b>	3 Year Limited	
<b>CERTIFICATIONS</b>	FCC Class B, CE, C-tick, RoHs	

